




SCAN ME

ASPHALT REPAIRS



AREAS OF APPLICATION

- Professionally restoring roads in all load categories
- Permanently restoring potholes
- Creating ramps
- Compensating for differences in levels
- Filling trenches
- Asphaltting around road fixtures (e.g. inlet grids, guide posts, guide rails, street lamps)
- Restoring small areas at entrances to houses, house driveways and parking spaces



AT A GLANCE



Road construction asphalt for every area of application

- ✓ Various grain size gradations
- ✓ Versatile
- ✓ Passable immediately after laying
- ✓ Hardens with water
- ✓ Maximum strength



ASPHALT REPAIRS

REPHALT® is a cold-processable and reactive-curing repair asphalt according to RVS 08.97.01 – for asphaltting work in small and large areas.



For optimum adhesion, pre-treatment with REAKTIV PRIMER* is recommended.

Mix **REPHALT®** homogeneously with approx. 2 M% water and then apply to the damaged area.

Use a rake or a trowel to lay the repair asphalt slightly above the surface.

Compact well using a tamper*. For larger areas, a roller or vibratory plate compactor is recommended.

PREREQUISITE

The substrate must be free from contamination, dust and grease. Can also be processed at temperatures just below 0°C.

CONSUMPTION

With an average installation thickness of 1 cm, one 25 kg bucket of **REPHALT®** is required for 1 m².

PRODUCT INFORMATION

Product	Packaging	Palletising
REPHALT® 0/4	25 kg bucket	24 buckets
REPHALT® 0/8	25 kg bucket	24 buckets
REPHALT® 0/2	25 kg bucket	24 buckets
REPHALT® 0/11	25 kg bucket	24 buckets
REPHALT® 0/4	14 kg bag	72 bags
REPHALT® 0/8	14 kg bag	72 bags
REPHALT® 0/2	14 kg bag	72 bags

*For sale from **VIALIT**



Compaction is decisive for durability of the restoration – depending on the installation thickness and maximum grain size, layer-by-layer application is recommended!

All tools used can be cleaned using cleaning agents commonly used in road construction.

After completion, the repaired area can be driven over again!

REPHALT® is available in grain sizes 0/2, 0/4, 0/8 and 0/11.



www.vialit.at