

STRADAKOL

COLOURED SURFACE SEALANT



SCAN ME




AT A GLANCE

Coloured surface sealant for asphalt and RESIST surfaces

- ✓ Can be processed cold
- ✓ Resistant to motor oils
- ✓ Weather resistant
- ✓ Optimum adhesion

AREAS OF APPLICATION

- Sealant for asphalt
- Sealant for gritted and non-gritted RESIST coatings
- Coloured marking on asphalt surfaces such as traffic areas, footpaths, cycle paths and car parks
- Coloured design of asphalt forecourts



STRADAKOL

COLOURED SURFACE SEALANT

STRADAKOL is a ready-to-use sealant.



1
Thoroughly clean the surface to be sealed and mask with a suitable adhesive tape*.



2
Stir thoroughly and homogeneously with a drill mixer before processing.



3
Apply with a rubber squeegee*. Then finish with a sealant roller.



4
When applying the material, ensure that it is processed evenly in strips.

PREREQUISITE

The substrate must be dry and free of impurities. The substrate and processing temperatures should be between + 10 °C and + 30 °C during the drying or curing period.

CONSUMPTION

For 1 m², approx. 0.6 – 1.5 kg of **STRADAKOL** should be used, depending on the substrate.

PRODUCT INFORMATION

Packaging: 15 kg
Palletising: 24 buckets/palett
Colours: on request!



i
Test the adhesion of substrates that have not been sealed with VIALIT materials! In the case of loose and poorly adhering coating residues, pre-treat the substrate (sanding, sandblasting or shot-blasting).

In dry, warm weather, the sealant is accessible to foot traffic after a few hours and rainproof after drying.

*To be obtained from **VIALIT**

www.vialit.at