

REFUG® 2K 5 kg unit




SCAN ME

JOINT SEALING COMPOUND



AREAS OF APPLICATION


- **Grouting joints, cracks and joints** on traffic surfaces of all load categories
- **Restoring grid cracks and expansion joints**
- **Restoring longitudinal joints** between concrete and asphalt
- **Restoring connection joints** (e.g. kerbstones, step treads and risers, paving stone and façade joints)
- **Filling induction loops**



AT A GLANCE

Cold-processable, elastic joint sealing compound in 5 kg unit

- ✓ Can be used both internally and externally
- ✓ Reactive-curing
- ✓ Short construction site closure times
- ✓ Can be processed manually



Vialit

Our product instructions constitute general guidelines, based on average values, and do not apply to applications under special conditions or stresses. Suitability for the intended purpose and local conditions must be verified in advance by the user. The processing instructions on the label must be observed. Approvals from employees are only accepted in the written form. We deliver and are liable exclusively on the basis of our Terms and Conditions of Sale and Delivery. Please refer to our safety data sheets for more information. Errors and omissions excepted. Illustrations and colours are not binding.

REFUG® 2K 5 kg unit

JOINT SEALING COMPOUND

REFUG® is a cold-processable, polymer-modified, high-quality sealing compound.




Stir component A thoroughly using a suitable stirring device and **then** stir in component B.



Homogenise the material until there are no visible white streaks.



Process the finished mixture quickly, as the curing process starts to happen quickly.



The filled joint can be sprinkled with chippings or sand.

PREREQUISITE

The substrate must be free from contamination, dust and grease. The material temperature must be between +15°C and +30°C during processing.

CONSUMPTION

Approx. 1 kg REFUG® corresponds to a volume of 1 dm³.

PRODUCT INFORMATION

Product	Packaging	Palletising
REFUG® 2K Component A	4.6 kg tin bucket	30/60 units of each component on 1 pallet
REFUG® 2K Component B	0.4 kg bottle	

i

For concrete joints, pre-treatment with REAKTIV PRIMER SPRAY* is recommended.

By choosing a suitable scattering sand, the filled joint can be colour-matched to its surroundings.

As REFUG® completely fills almost all cavities of a joint, re-pouring may be necessary.



*For sale from VIALIT

www.vialit.at

Vialit

VIALIT ASPHALT GmbH & Co.KG
5280 Braunau am Inn \ Josef-Reiter-Str. 78
T +43 7722 62977-0
www.vialit.at \ office@vialit.at
Zertifiziert nach ISO 9001

